**Windows®. Life without Walls™.**
**Fujitsu recommends Windows 7.**

# DATA SHEET
# FUJITSU CELSIUS M470 WORKSTATION

## YOUR NEW "THOROUGHBRED" WORKSTATION

The CELSIUS M Series is the single-processor platform with a particularly well-balanced ratio between price and performance. The CELSIUS M470 incorporates the latest advances in performance technologies enabling you to meet increasingly demanding schedules using professional applications such as CAD/CAE, virtual reality and finance.

**PERFORMANCE**
Higher productivity
- High performance multi-core processors, hard disk drives and next generation graphics subsystems

**ERGONOMICS**
Quiet system for a pleasant working environment
- Optimized thermal management, low-noise chassis and silent fans

**RELIABILITY**
System stability for the complete lifecycle
- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

**CERTIFICATION OF WORKSTATION APPLICATIONS**
Stability, compatibility and performance for the main workstation applications
- Comprehensive support for ISV applications and ease of integration into existing IT networks

**EXPANDABILITY**
Excellent expandability for future demands
- Increased memory capacities of up to 24 GB

**Windows®. Life without Walls™.**
**Fujitsu recommends Windows 7.**

# COMPONENTS

| | |
|---|---|
| **PROCESSOR** | Intel® Xeon® processor X5680 (6C, 3.33 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5677 (4C, 3.46 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5670 (6C, 2.93 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5667 (4C, 3.06 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5660 (6C, 2.80 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5650 (6C, 2.66 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5570 (4C, 2.93 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5560 (4C, 2.8 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor X5550 (4C, 2.66 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor W5590 (4C, 3.33 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor W5580 (4C, 3.2 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor W3680 (6C, 3.33 GHz, 12 MB, 6.4 GT/s) |
| | Intel® Xeon® processor W3580 (4C, 3.33 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor W3570 (4C, 3.2 GHz, 8 MB, 6.4 GT/s) |
| | Intel® Xeon® processor W3565 (4C, 3.20 GHz, 8 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3550 (4C, 3.06 GHz, 8 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3540 (4C, 2.93 GHz, 8 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3530 (4C, 2.80 GHz, 8 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3520 (4C, 2.66 GHz, 8 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3505 (2C, 2.53 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3503 (2C, 2.5 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor L5640 (6C, 2.26 GHz, 12 MB, 5.86 GT/s) |
| | Intel® Xeon® processor L5630 (4C, 2.13 GHz, 12 MB, 5.86 GT/s) |
| | Intel® Xeon® processor L5609 (4C, 1.86 GHz, 12 MB, 5.86 GT/s) |
| | Intel® Xeon® processor L5530 (4C, 2.40 GHz, 8 MB, 5.86 GT/s) |
| | Intel® Xeon® processor L5520 (4C, 2.26 GHz, 8 MB, 5.86 GT/s) |
| | Intel® Xeon® processor L5506 (4C, 2.13 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor E5640 (4C, 2.66 GHz, 12 MB, 5.86 GT/s) |
| | Intel® Xeon® processor E5630 (4C, 2.53 GHz, 12 MB, 5.86 GT/s) |
| | Intel® Xeon® processor E5620 (4C, 2.40 GHz, 12 MB, 5.86 GT/s) |
| | Intel® Xeon® processor E5540 (4C, 2.53 GHz, 8 MB, 5.86 GT/s) |
| | Intel® Xeon® processor E5530 (4C, 2.4 GHz, 8 MB, 5.86 GT/s) |
| | Intel® Xeon® processor E5520 (4C, 2.26 GHz, 8 MB, 5.86 GT/s) |
| | Intel® Xeon® processor E5507 (4C, 2.26 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor E5506 (4C, 2.13 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor E5504 (4C, 2.0 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor E5503 (2C, 2.00 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor E5502 (2C, 1.86 GHz, 4 MB, 4.8 GT/s) |
| | Intel® Xeon® processor W3670 (6 Cores / 12 Threads, 3.20 GHz, 12 MB) |

| | |
|---|---|
| **OPERATING SYSTEM** | |
| **Operating system optional preinstalled** | Genuine Windows® 7 Professional 64-bit<br>Genuine Windows® 7 Professional 32-bit |
| **Operating system compatible** | Genuine Windows® XP Professional x64 Edition<br>Genuine Windows® XP Professional<br>Linux |
| **Operating system notes** | Red Hat® certification<br>Novell® certification<br>For some configurations third party drivers are currently not available or configuration restrictions may apply. |

| | |
|---|---|
| **MEMORY MODULES** | 1 GB (1 module(s) 1 GB) DDR3, 1333 MHz, PC3-10600 |
| | 1 GB (1 module(s) 1 GB) DDR3, ECC, 1333 MHz, PC3-10600 |
| | 2 GB (1 module(s) 2 GB) DDR3, ECC, 1333 MHz, PC3-10600 |
| | 4 GB (1 module(s) 4 GB) DDR3, ECC, 1333 MHz, PC3-10600 |
| **GRAPHICS ADD ON CARDS (OPTIONAL)** | Remote Graphics: CELSIUS RemoteAccess Card, PCIe x1, 2x DVI-I |
| | Ultra-high-end 3D: NVIDIA® Quadro® FX 4800, 1.5 GB, PCIe x16, 2x DL-DVI-I, 2x DP |
| | Ultra-high-end 3D: ATI FirePro™ V7800, PCIe x16, DL-DVI-I, 2x DP |
| | High-end 3D: NVIDIA® Quadro® FX 3800, 1024 MB, PCIe x16, DL-DVI-I, 2x DP |
| | High-end 3D: ATI FirePro™ V7750, 1024 MB, PCIe x16, 2x DP, 1x DVI-I |
| | High-end 3D: ATI FirePro™ V5800, PCIe x16, DL-DVI-I, 2x DP |
| | Midrange 3D: NVIDIA® Quadro® FX 1800, 768 MB, PCIe x16, DL-DVI-I, 2x DP |
| | Midrange 3D: NVIDIA® Quadro® FX 580, 512 MB, PCIe x16, DL-DVI-I, 2x DP |
| | Midrange 3D: ATI FirePro™ V4800, PCIe x16, DL-DVI-I, 2x DP |
| | Entry 3D: NVIDIA® Quadro® FX 380, 256 MB, PCIe x16, 2x DL-DVI-I |
| | Entry 3D: ATI FirePro™ V3800, PCIe x16, DL-DVI-I, DP |
| | Multi monitor 2D: NVIDIA® Quadro® NVS 295, 256 MB, PCIe x1, 2x DP |
| | Multi monitor 2D: 2nd NVIDIA® Quadro® NVS 295, 256 MB, PCIe x1, 2x DP |
| | Professional 2D: NVIDIA® Quadro® NVS 450, 512 MB, PCIe x16, 4 x DP |
| | Professional 2D: NVIDIA® Quadro® NVS 295, 256 MB, PCIe x16, 2x DP |
| | Professional 2D: NVIDIA® Quadro® NVS 290, 256 MB, PCIe x16, 2x SL DVI-I |
| | Professional 2D: NVIDIA® Quadro® NVS 290, 256 MB, PCIe x1, 2x SL DVI-I |
| **HARD DISK DRIVES (INTERNAL)** | SSD SATA, 256 GB, 2.5-inch |
| | SSD SATA, 128 GB, 2.5-inch |
| | SATA III, 10000 rpm, 600 GB, 3.5-inch internal |
| | SATA II, 10000 rpm, 300 GB, 2.5-inch, S.M.A.R.T. |
| | SATA II, 10000 rpm, 150 GB, 2.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 2000 GB, 3.5-inch, S.M.A.R.T. business critical |
| | SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. business critical |
| | SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 750 GB, 3.5-inch, S.M.A.R.T. business critical |
| | SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical |
| | SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. |
| | HDD SAS, 15000 rpm, 600 GB, 3.5-inch internal |
| | HDD SAS, 15000 rpm, 450 GB, 3.5-inch |
| | HDD SAS, 15000 rpm, 300 GB, 3.5-inch |
| **Hard disk notes** | 2.5-inch drives will be mounted in the 3.5-inch bays<br>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. |
| **DRIVES (OPTIONAL)** | Blu-ray Disc™ Triple Writer |
| | DVD-ROM |
| | DVD Super Multi |
| | MultiCard Reader 20in1, 3.5-Inch |
| **INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)** | |
| | WLAN III, 802.11g/Draft-n (Windows only) |
| | Parallel Interface |
| | Gigabit Ethernet PCIe x1 |
| | eSATA Interface |
| | Dual serial card PCI |

| | | |
|---|---|---|
| **Base unit** | CELSIUS M470-2 | CELSIUS M470-2 POWER |

| | | |
|---|---|---|
| **MAINBOARD** | | |
| **Mainboard type** | D2778 | |
| **Formfactor** | ATX | |
| **Chipset** | Intel® X58 Express, Intel® 82801JR ICH10R | |
| **Processor socket** | LGA 1366 | |
| **Processor quantity maximum** | 1 | |
| **Memory slots** | 6 DIMM | |
| **Supported capacity RAM (max.)** | 24 GB | |
| **Memory notes** | In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration). | |
| **LAN** | Built-in 10/100/1000 MBit/s Realtek RTL8111 | |
| **Audio codec** | Realtek ALC663 | |
| **Audio features** | High Definition Audio | |
| **I/O CONTROLLER ON BOARD** | | |
| **Serial ATA total** | 6 | |
| **SATA RAID support** | 0, 1, 10, 5 | |
| **INTERFACES** | | |
| **Audio: in (rear)** | 1 | |
| **Audio: out / SPDIF (rear)** | 2 / 1 | |
| **Front Audio: in** | 1 | |
| **Front Audio: out** | 1 | |
| **FireWire (IEEE1394) (front)** | 1 | |
| **FireWire (IEEE1394) (rear)** | 1 | |
| **Internal speakers** | 1 | |
| **USB 2.0 total** | 11 | |
| **USB front** | 2 | |
| **USB rear** | 6 | |
| **USB internal** | 3, thereof 1 type A | |
| **Serial (RS-232)** | 1 | |
| **Mouse / Keyboard (PS/2)** | 1 / 1 | |
| **Ethernet (RJ-45)** | 1 | |
| **Interface Module notes** | Anytime USB charge functionality | |
| **DRIVE BAYS** | | |
| **Drive bays total** | 7 | |
| **3.5-inch internal bays** | 4 | |
| **5.25-inch external bays** | 3 | |
| **SLOTS** | | |
| **PCI-Express 2.0 x16** | 2 x (312 mm) full height | |
| **PCI-Express 1.0 x4 (mech. x8)** | 1 x (312 mm) full height | |
| **PCI-Express 2.0 x4 (mech. x8)** | 1 x (312 mm) full height | |
| **PCI (32-bit / 33 MHz)** | 2 x (312 mm) full height | |
| **ELECTRICAL VALUES** | | |
| **Power consumption note** | 190 W depending on configuration | 190 W depending on configuration |
| **Rated voltage range** | 100 - 240 V | 100 - 240 V |
| **Rated frequency range** | 50 - 60 Hz | 50 - 60 Hz |
| **Max. output of single power supply** | 500 W up to 85% efficiency | 700 W up to 85% efficiency |
| **NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)** | | |
| **Noise emission** | According to ISO9296 (LpAm at bystander position) | |
| **Idle mode** | 23 dB(A) | |
| **Office mode** | 23 dB(A) | |
| **Noise notes / description** | depending on configuration | |

| | | |
|---|---|---|
| **DIMENSIONS / WEIGHT / ENVIRONMENTAL** | | |
| **Dimensions (W x D x H)** | 215 x 522 x 446 mm | |
| **Operating position** | Vertical / horizontal | |
| **Weight** | 18 kg | |
| **Weight notes** | Actual weight may vary depending on configuration | |
| **Operating ambient temperature** | 15 - 35°C | |
| **Operating relative humidity** | 10 - 75 % | |
| **COMPLIANCE** | | |
| **Product** | CELSIUS M470-2 | CELSIUS M470-2 POWER |
| **Model** | MCS-D2778 | MCS-D2778 |
| **Germany** | GS<br>depending on configuration<br>Blauer Engel / Blue Angel | GS<br>depending on configuration |
| **Europe** | CE | CE |
| **USA/Canada** | cCSAus<br>FCC Class B | cCSAus<br>FCC Class B |
| **Global** | RoHS (EU & China)<br>ENERGY STAR® 5.0<br>Medical EMC standard IEC60601-1-2 in combination with medical kit | RoHS (EU & China)<br>ENERGY STAR® 5.0<br>Medical EMC standard IEC60601-1-2 in combination with medical kit |
| **China** | CCC | CCC |
| **Compliance link** | https://sp.ts.fujitsu.com/sites/certificates/default.aspx | https://sp.ts.fujitsu.com/sites/certificates/default.aspx |
| **SECURITY** | | |
| **Physical security** | Kensington Lock support<br>Eye for padlock<br>Seal option<br>Intrusion switch<br>Optional: Integrated cabinet lock | |
| **System security** | Write protect option for the Flash EPROM<br>Boot protection for floppy disk / CD drive and write protection for floppy disk drive<br>Dynamic USB security for full hardware USB protection<br>Control of all USB interfaces<br>External USB interfaces detachable separately<br>Embedded security (TPM 1.2) - Infineon | |
| **User security** | Optional: Access protection via internal SmartCard reader<br>User and supervisor BIOS password<br>Optional: SmartCase Logon+ | |
| **ADDITIONAL SOFTWARE** | | |
| **Additional software (optional)** | Drivers & Utilities DVD (DUDVD) Windows® 7 & Vista & XP<br>CyberLink PowerDVD 9<br>Nero 9 Essentials XL<br>Recovery DVD (Windows® 7)<br>Windows® XP 64 downgrade pack<br>Windows® XP 32 downgrade pack | |
| | Keyboard on (Special Fujitsu keyboard required)<br>Thermal management | Keyboard on (Special Fujitsu keyboard required)<br>Thermal management |
| **Spare part availability** | 5 years | 5 years |
| **MANAGEABILITY** | | |
| **Manageability features** | DeskUpdate Driver management | |
| **Manageability type** | DeskView 10.x client management including:<br>DASH 1.1 remote system management | |
| **DeskView features** | On/Offline remote client management<br>Detailed system inventory management and reports<br>BIOS Management<br>Remote power management<br>System notifications<br>Security Remote Control<br>DeskView Helpdesk Integration | |

| | |
|---|---|
| **MANAGEABILITY** | |
| **Supported standards** | WMI<br>BootP (made4you)<br>PXE<br>WoL (Wake on LAN) |
| **Manageability link** | http://ts.fujitsu.com/manageability |
| **INPUT DEVICE / COMPONENTS** | |
| | Optical USB tilt wheel mouse |
| **Input devices (optional)** | Optical USB/PS2 tilt wheel mouse<br>Space Explorer USB<br>Space Navigator USB<br>Space Pilot USB<br>Keyboard |
| **WARRANTY** | |
| **Standard Warranty** | 3 years (depending on country) |
| **Service level** | On-site Service (depending on country) |
| **MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION** | |
| **Recommended Service** | 5x9, Response Time: Next Business Day |
| **Service Weblink** | http://ts.fujitsu.com/Supportservice |

**Windows®. Life without Walls™.**
**Fujitsu recommends Windows 7.**

## FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu CELSIUS M470, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

**Dynamic Infrastructures**
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

**Computing Products**
www.fujitsu.com/global/services/computing/

**Software**
www.fujitsu.com/software/

## MORE INFORMATION

Learn more about Fujitsu CELSIUS M470, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://ts.fujitsu.com/celsius

## FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Green Policy Innovation

## COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

## DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

## CONTACT

FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2010-10-21 CE-EN